

SOLID PVC

APPLICABLE

- In public and domestic buildings
- In heated, inhabited rooms
- In roof pitch range of 15°-90°
- Suitable on all common roofings with proper flashing

FEATURES

- Centre pivot u-PVC roof window
- Toughened outer glass
- Excellent insulation
- High humidity resistance
- Maintenance free PVC profile
- Elegant bottom handle
- Two passive ventilation positions via handle
- Double gasket system between frame and sash
- Double Low-e coating
- Easy installation
- 10 year guarantee

MATERIAL

- Lead free PVC
- Steel reinforcement
- Polystyrene insulation insertion

COVER PARTS

- Aluminium, lacquered, grey colour (RAL 7043)

HANDLE

- Ergonomically designed moulded zinc handle, lacquered

HINGE

- Pivot hinge



CE



APY B900

PANE

Construction	4-16-4H
Thickness of glazing (mm)	24 mm
Low E	■ ■
Gas	Argon
Toughened	■
$U_g (W/m^2K)$	1.0
Total solar energy transmittance	0.55

WINDOW

$U_w (W/m^2K)$	1.3
Water tightness	E1500
Air permeability	Class 4
Resistance to wind load	Class C4
Sound reduction	32 (-1,-5) dB

COLOUR

White	■
-------	---

MEASURES

CODE	NOMINAL SIZE	FRAME EXTERNAL SIZE		PANE SIZE		VISIBLE GLASS		
		Width	Height	Width	Height	Width	Height	Effective Light Area m ²
C2A	55 x 78 cm	55 cm	77,8 cm	39,8 cm	64,9 cm	37,3 cm	59 cm	0.220
F6A	66 x 118 cm	66 cm	117,8 cm	50,8 cm	104,9 cm	48,3 cm	99 cm	0.478
M4A	78 x 98 cm	78 cm	97,8 cm	62,8 cm	84,9 cm	60,3 cm	79 cm	0.476
M6A	78 x 118 cm	78 cm	117,8 cm	62,8 cm	104,9 cm	60,3 cm	99 cm	0.597
M8A	78 x 140 cm	78 cm	139,8 cm	62,8 cm	126,9 cm	60,3 cm	121 cm	0.729

FLASHING RANGE FOR DIFFERENT ROOFING MATERIALS **



UFX

UNIVERSAL
Suitable for high profiled tiles
and profiled materials between
16-120 mm

BLIND RANGE *



DUA

BLACKOUT



MIA

AWNING



*For the right product code of blinds, please take the type of blind, size of RW and colour code, e.g. DUA C2A 4219